



40' Flat Rack Containers



We Specialize.

A fleet of over one million TEU's of dry van and refrigerated containers plus a full range of specialized containers: palletwides, flat racks, open tops, swap bodies, roll trailers and railcars. We have the equipment you need for intermodal transport, and the logistical expertise to put it work.

Find out more at <http://www.capps.com/equipment>

ANTWERP

John Pacey

Theater Building
Molenbergstraat 10,
Box 7 (19th Floor)
2000 Antwerp,
Belgium

T 32-3-685-1700
E jpacey@capps.com

GENOA

Silvio Como

Genoa Logistic Services S.r.l.
Via Pietro Chiesa 07, 8th floor
16149 Genoa GE
Italy

T 39-010-4694011
F 39-010-6435352
E genoalog@glssrl.com

HAMBURG

Hendrik Wehlen

Neuer Wall 84
20354 Hamburg
Germany

T +49-(0)40-32 96 96 8-0
F +49-(0)40-32 96 96 8-99
E hwehlen@capps.com

LONDON

John Pacey

Kingsgate
1 King Edward Road
Brentwood Essex, CM14 4HG
UK

T 44-1277-223-666
F 44-1277-223-668
E jpacey@capps.com

NEW JERSEY

John Pearson

P.O. Box 8471
Red Bank, NJ 07701
U.S.A.

T 914-319-7383
F 415-788-3430
E jpearson@capps.com

NEW JERSEY

Amanda Gatzke

P.O. Box 438
Florham Park, NJ 07932
U.S.A.

T 973-377-9103
F 973-377-9319
E agatzke@capps.com

SAN FRANCISCO

Karen Szeto

Steuart Tower, 1 Market Plaza
Suite 900
San Francisco, CA 94105
U.S.A.

T 415-788-0100
F 415-788-3430
E kszeto@capps.com



40' Flat Rack Containers

GENERAL SPECIFICATIONS:

	40' Flat Rack Containers
External	
LENGTH (Base Corner Casting)	12,192 mm
LENGTH (Tare condition, top castings)	12,202 mm max
LENGTH (Loaded to R, top castings)	12,172 mm min
WIDTH (Base bottom castings)	2,438 mm
HEIGHT (End frame erected)	2,591 mm
HEIGHT (End frame folded)	648 mm
Internal	
LENGTH (Between corner posts)	11,652 mm
WIDTH (Over bottom side rail)	2,374 mm
HEIGHT (side rail adjacent to post top castings)	1,959 mm
Camber	
	50 mm (after preloading)
Stack Height	
	Folds 4 into 2,591 mm
Payload	
	47,400 kg
Tare Weight	
	5,100 kg
Max Gross Weight	
	52,500 kg
Floor Strength	
	7,260 kg
Gooseneck	
	YES



40' Flat Rack Containers - (End frame erected)



40' Flat Rack Containers (End frame folded)

Handling Devices

- 1, Lifting, full or empty, at the top corner fittings vertically by means of spreaders fitted with hooks, shackles or twistlocks.
- 2, Lifting, full or empty, at the bottom corner fittings using slings with appropriate terminal fittings at slings angle of thirty (30) degrees to horizontal.
- 3, Lifting, empty only, from a set of Forklift pockets.

Stacking

8 high at 30,480 kg or 5 high at 52,500 kg gross.

Dimensions and ratings within normal manufacturing tolerances. Measurements and weights may vary slightly for individual series.