



40' Open Top Containers



We Specialize.

A fleet of over one million TEU's of dry van and refrigerated containers plus a full range of specialized containers: palletwides, flat racks, open tops, swap bodies, roll trailers and railcars. We have the equipment you need for intermodal transport, and the logistical expertise to put it work.

Find out more at <http://www.capps.com/equipment>

ANTWERP

John Pacey

Theater Building
Molenbergstraat 10,
Box 7 (19th Floor)
2000 Antwerp,
Belgium

T 32-3-685-1700

E jpacey@capps.com

GENOA

Silvio Como

Genoa Logistic Services S.r.L.
Via Pietro Chiesa 07, 8th floor
16149 Genoa GE
Italy

T 39-010-4694011

F 39-010-6435352

E genoalog@glssrl.com

HAMBURG

Hendrik Wehlen

Neuer Wall 84
20354 Hamburg
Germany

T +49-(0)40-32 96 96 8-0

F +49-(0)40-32 96 96 8-99

E hwehlen@capps.com

LONDON

John Pacey

Kingsgate
1 King Edward Road
Brentwood Essex, CM14 4HG
UK

T 44-1277-223-666

F 44-1277-223-668

E jpacey@capps.com

NEW JERSEY

John Pearson

P.O. Box 8471
Red Bank, NJ 07701
U.S.A.

T 914-319-7383

F 415-788-3430

E jpearson@capps.com

NEW JERSEY

Amanda Gatzke

P.O. Box 438
Florham Park, NJ 07932
U.S.A.

T 973-377-9103

F 973-377-9319

E agatzke@capps.com

SAN FRANCISCO

Karen Szeto

Steuart Tower, 1 Market Plaza
Suite 900
San Francisco, CA 94105
U.S.A.

T 415-788-0100

F 415-788-3430

E kszeto@capps.com



40' Open Top Containers

GENERAL SPECIFICATIONS:

	40' Open Top Containers
External	
LENGTH	12,192 mm
WIDTH	2,438 mm
HEIGHT	2,591 mm
Internal	
LENGTH	12,032 mm
WIDTH	2,352 mm
HEIGHT	2,348 mm
Door Opening	
WIDTH	2,340 mm
HEIGHT	2,280 mm
Roof Opening	
WIDTH	2,232 mm
LENGTH	11,806 mm
Swing Header Opening	
WIDTH	1,940 mm
Inside Cubic Capacity	
	65.9 cu. M
Payload	
	26,680 kg
Tare Weight	
	3,800 kg
Max Gross Weight	
	30,480 kg
Cubic Capacity	
	79,6 cbm
Floor Strength (ISO 1+1/3)	
	7,260 kg



40' Open Top Containers



40' Open Top Containers

Stacking

On Deck, 4 high stacking (based on MGW 30,480 kg),
On Cell, 7 High stacking (based on MGW 30,480 kg).

Dimensions and ratings within normal manufacturing tolerances. Measurements and weights may vary slightly for individual series. Priority design is with three Omega centre rails as floor spacer.